



ODR 100

Features:

- Light weight and versatile
- Quickly converts from ATV towing to man portable
- Operator Friendly controls - designed and built with the driller in mind
- Guarding exceeds industry standards
- Modular build for ease of helicopter mobilization and difficult to access projects
- Proven and tested for reliability in extreme environments and difficult drilling conditions



Depth Rating

A0 450 m (1500 ft)

B0 290 m (950 ft)

N0 230 m (750 ft)



Rotation Speed	<ul style="list-style-type: none"> • 1350 RPM
Rotation Unit Options	<ul style="list-style-type: none"> • Top Drive A0 • Hollow Spindle B0 • Hollow Spindle N0
Power Unit Options	<ul style="list-style-type: none"> • Kubota / Lambardini • 43 HP @ 3200 RPM • Conforms to EPA standards
Mast	<ul style="list-style-type: none"> • Telescopic Design • 1.5M Pull Back (stroke) • 15000 LBS Pullback • Hydraulic Setup
Foot Clamp	<ul style="list-style-type: none"> • Reliable and practical - 2 jaw design • N0 Capacity
Wireline Hoist	<ul style="list-style-type: none"> • Hydraulic 300m (1000 ft) - 3/16" cable capacity
Hydraulic System	<ul style="list-style-type: none"> • High quality pressure compensated hydraulic system with industry leading filtration • Hydraulic mud mixer
Optional Equipment	<ul style="list-style-type: none"> • 10 HP Diesel powered 420 flush pump







